

sewoo

Robust and durable label mobile printers

LK-P30II



- Fast Print Speed
- Excellent Compatibility
- Quick and easy to support peel mode
- Rugged design for Drop resistant
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Car Charger



WiFi



Bluetooth



Barcode



Portable



Durable



Rugged
Design



Drop
Resistant



Wireless
Connectivity



Easy
Loading



Fast
Speed



Compact
Design



Easy
Maintenance



Improved
Battery Life



S-MDM
Support



APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
Up to 3,9ips (100mm/sec)

Print Width
Up to 2.8" (72mm)

Resolution
203 dpi (8dots/mm)

Memory
8MB SDRAM,
16MB(Max.32MB) Flash

Battery Voltage / Capacity
7.4V / 2600mAh.
Rechargeable Li-ion battery

Battery Charge Time
3.3Hrs

Standby Time
100Hrs

Sensor
Paper end, Black mark,
Cover open, Gap

Reliability
TPH life : 50km



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
4.72" x 5.98" x 2.75"
(120 x 152 x 70mm)

Weight
1.4lb(640g, Battery Incl.)



INTERFACES

Standard
USB, Serial(RS-232C)

Option
Wi-Fi(802.11a/b/g/n), Bluetooth Smart
Ready (Bluetooth4.2+BLE)



CERTIFICATIONS

KC, CE, FCC, UL/cUL, IC, Mfi, UKCA



OPERATING CHARACTERISTICS

Operating Temperature
14 ~ 122°F (-10 ~ 50°C)

Operating Humidity
10 ~ 80%

Storage Temperature
-4 ~ 140°F (-20 ~ 60°C)

Storage Humidity
10 ~ 90%

Dust-and Water-resistance Rating
IP42(Set only), IP54(With case)

Drop Rating
3.9ft(1.2m, Set only), 5.9ft(1.8m, With case)



BARCODES

1D
EAN-8, EAN-8(+2+5), EAN-13,
EAN-13(+2+5), Codabar, Code11,
Code39, Code93, Code128, ITF,
LUPC-A(+2+5), UPC-E, UPC-E(+2+5),
Planet, UPC-A etc

2D
QR, PDF417, MicroPDF417, Maxicode,
Datamatrix, Aztec, RSS14, TLC39



SOFTWARE

Emulations
ESC/POS, CPCL, ZPL/EPL Command
compatible

Drivers
Windows Driver(10, 2012, 8, 7, 2008,
VISTA, 2003, XP, 32bit & 64bit),
Window CE & Mobile Driver & SDK
(CE 4.2~, Mobile 5.0~), Linux Driver,
Mac Driver, OPOS Driver, JavaPOS Driver,
iOS SDK, Android(2.1~) SDK



MEDIA CHARACTERISTICS

Media Type
Thermal paper/label

Media Width
0.9" ~ 3.1" (25~80mm)

Media Core Diameter
Ø 0.4" (12.5mm)

Media Roll Diameter
Ø 2.2" (56mm)

Thickness
0.06 ~ 0.16mm



FONTS / GRAPHICS

Character Type
Font A(12x24), Font B(9x17),
Asian Font(KOR,JPN,CHN-GB2312,
CHNBig5), Font0/1/2/4/5/6/7,
Resident TTF, Downloadable TTF,
FontA~H, FontGS, Resident TTF(Font0),
Font 1~8

Characters per Line (CPL)
Font A(12x24): 48cpl,
Font B(9x17): 64cpl,

Character Set
95 Alphanumeric,
14 International,
128 x 18 Graphic



ACCESSORIES

Standard
USB Cable, Battery Pack, Serial Cable
Thermal Roll Paper, Belt Buckle,
Battery Charger (8.4V)

Optional
Battery Cradle, Vehicle Charger,
Leather Case, Shoulder Strap



Bnext

Monterrey | Chihuahua | Ciudad de México | Guadalajara | Mazatlán

Tel. +52 (81) 8881 1080 Ext 1004 Cel. +52 (81) 2747 6654 E-mail. lcardenas@bnext.mx