sewoo

It's a totally convenient mobile presented by
Advanced Manual Cutter

LK-P24
LK-P34

LK-P34
FOR 3 INCH

LK-P24
FOR 2 INCH

- Fast Print Speed : 4 ips
- AMC (Advanced Manual Cutter) supproted
  - By Pushing a button, Easily paper cut
- Excellent compatibility
- NFC for easy Bluetooth pairing
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Belt Strap, Car Charger

WiFi | Bluetooth | Barcode | Portable | Durable

Rugged Design | Drop Resistant | Wireless Connectivity | Easy Loading | Fast Speed (100 mm/sec) | Compact Design | Easy Maintenance | Improved Battery Life | S-MDM Support

APPLICATION

SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method
Direct thermal
Print Speed
Up to 3.9ips (100mm/sec)
Print Width
LK-P24 : Up to 1.8” (48mm)
LK-P34 : Up to 2.8” (72mm)
Resolution
203 dpi (8dots/mm)
Memory
LK-P24 : 8MB SRAM, 8MB Flesh
LK-P34 : 8MB SRAM (MAX.16MB)
8MB Flesh (MAX.16MB)
Battery Voltage / Capacity
Rechargeable Li-ion battery
LK-P24 : 7.4V / 1,450mAh
LK-P34 : 7.4V / 2,000mAh
Battery Charge time
LK-P24 : Max. 1.7Hrs
LK-P34 : Max. 2.7Hrs
Standby Time
LK-P24 : Max. 36Hrs
LK-P34 : Max. 61Hrs
Sensor
LK-P24 : Paper end, Black mark sensor
LK-P34 : Paper end, Black mark sensor
Reliability
TPH life : 50km

PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
LK-P24 : 3.2”×4.77”×1.78”
(81.5 x 121.4 x 45.3mm)
LK-P34 : 4.23”×5.70”×2.20”
(107.5 x 145 x 56mm)
Weight
LK-P24 : 0.5lb(0.2kg, With battery)
LK-P34 : 0.9lb(0.4kg, With battery)

MEDIA CHARACTERISTICS

Media Type
Thermal paper
Media Width
LK-P24 : 2.2” (58mm)
LK-P34 : 3.1” (80mm)
Paper guide (58mm)
Media Core Diameter
0.4” (12.5mm)
Media Roll Diameter
1.5” (40mm)
LK-P24 : ø40
LK-P34 : ø50
Thickness
0.06mm

OPERATING CHARACTERISTICS

Operating Temperature
14~122°F(-10 ~ 50°C)
Operating Humidity
10 ~ 80%
Storage Temperature
-4~140°F(-20 ~ 60°C)
Storage Humidity
10 ~ 90%
Dust-and Water-resistance Rating
LK-P24 : IP43
LK-P34 : IP54
Drop Rating
5ft/1.5m (set only) to concrete

BARCODES

1D
EAN-8, EAN-8(+2+5), EAN-13, EAN-13(+2+5), Codabar, Code11, Code39, Code93, Code128, ITF, LUPC-A(+2+5), UPC-E, UPC-E(+2+5), Planet, UPC-A etc
2D
QR, PDF417, MicroPDF417, Maxicode, Datamatrix, Aztec, RSS14, TLC39

CERTIFICATIONS

KC, CE, FCC, UL/cUL, Mfi, UKCA

SOFTWARE

Emulations
ESC / POS, CPCL, ZPL Command compatible
Drivers
Windows Driver(10, 2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Window CE & Mobile Driver & SDK (CE 4.2~, Mobile 5.0~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1~) SDK

ACCESSORIES

Standard
LK-P24 : USB cable, Battery pack, Thermal roll paper, Belt strap & Bracket, Battery Charger (8.4V)
LK-P34 : USB Cable, Battery pack, Thermal roll paper, Belt strap, Battery Charger (8.4V)
Option
LK-P24 : Set cradle, Leather case + Shoulder Strap
LK-P34 : 4bay cradle, Battery cradle, Shoulder Strap, Leather Case

FONTS / GRAPHICS

Character Type
Font A(12×24), Font B(9×17), Asian Font (KOR, JPN, CHN-GB2312, CHN-Big5), Font0/1/2/4/5/6/7, Resident TTF , Downloadable TTF, FontA~H, FontGS, Residnt TTF(Font0), Font 1~8
Characters per line (CPL)
LK-P24: Font A(12x24): 32cpl,
Font B(9x17): 42cpl,
LK-P34: Font A(12x24): 48cpl,
Font B(9x17): 64cpl,
Character set
95 Alphanumeric, 14 International, 128 x 18 Graphic

INTERFACES

Standard
USB 2.0
Bluetooth Smart Ready (BT4.2+BLE)
Wi-Fi (802.11 a/b/g/n/ac) Combo
- TKIP and AES encryption
- WPA and WPA2
- 802.1x (with WPA or WPA2)
- EAP-TTLS, EAP-TLS, PEAP (MSCHAPv2)
- Supports Certificates and Private Key (PEM) Upload
- Support for Soft AP, Infrastructure Mode NFC for easy Bluetooth pairing

Bnext®
Monterrey | Chihuahua | Ciudad de México | Guadalajara | Mazatlán
Tel. +52 (81) 8881 1080 Ext 1004 Cel. +52 (81) 2747 6654 E-mail. lcardenas@bnext.mx