



DOT IMPACT PRINTER

SLK-D30

- Drop-in paper loading
- 4.7 Lines/sec high speed printing
- Two color printing
- Auto cutter (optional)
- Paper end / Cover open / Paper low sensor
- Black mark sensor (optional)





EASY PAPER LOADING




BACK SIDE



SPECIFICATION

ITEM		TYPE
MODEL		SLK-D30
PRINTING	METHOD	9-pin Serial Dot Impact Matrix
	DIRECTION	Bi-directional (with logical seeking)
	SPEED	4.7 lines/sec
	WIDTH	63.5mm
	LINE SPACING	n/144inch
	RESOLUTION	160DPI / 80DPI
	NO. OF COLUMNS	TM-U200 Emulation : 42/35, 40/33 Other Emulation : 40/33
PAPER	NO. OF TOTAL DOTS	400 dots/line
	FONT SIZE	7x9, 9x9 / 5x9, 7x9
	TYPE	Roll paper
	WIDTH	57.5mm, 69.5mm, 76.2mm
INK RIBBON	DIAMETER	MAX. 80mm
	COPIES	Original + 2copies
RELIABILITY		ERC-38 Compatible (Black, Purple, Black/Red)
PRINT HEAD	PRINT HEAD	18million lines
	MCBF	120million characters
AUTO CUTTER		1,000,000cuts(guillotine)
INTERFACE		Serial, Parallel, USB, Ethernet, Combo(USB+Serial)
EMULATION		TM-U200, TM-U300, iDP-3540, SP200 Command Compatible
DRIVER		Windows Driver(2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Linux, OPOS, JavaPOS, WEPOS Driver
POWER	TYPE	External SMPS
	AC	100 ~ 240Vac 50/60 Hz
	DC	24Vdc / 2.5A
TEMPERATURE	OPERATION	0 ~ 45°C
	STORAGE	-20 ~ 60°C
DIMENSION		156mm x 243.2mm x 150mm (W x D x H)
WEIGHT		2.38kg (Cutter included)
COLOR		Cool grey, Ivory

● All specification and desings are subject to change without notice.



Monterrey | Chihuahua | Ciudad de México | Guadalajara | Mazatlán

Tel. +52 (81) 8881 1080 Ext 1004 Cel. +52 (81) 2747 6654

E-mail. lcardenas@bnext.mx