

POS PRINTER



SLK-T42

- Compact Size
- Tear bar type / Auto cutter (optional)
- Dual interface : USB + Serial
- High speed printing : 200mm/sec

APPLICATIONS



Shopping



Mart



Airport



Hospital



Coffee Shop



Bank



Restaurant



Ticketing



Parking



Lottery




Election



sewoo

2inch Compact size Thermal Printer

SLK-T42



Item			Specification		Item		Specification	
PRINTING	METHOD	Direct Thermal			SENSOR		Paper End, Cover Open	
	SPEED	Max. 200mm/sec			CASH DRAWER DRIVER		2 circuits (24V, 1A max)	
	WIDTH	54mm(432 Dots/Line)			INTERFACE		USB(A type)+Serial(RS-232C) Built-in	
	RESOLUTION	203DPI			EMULATION		ESC/POS Command Compatible	
	DOT PITCH(mm)	0.125mm x 0.125mm			DRIVER		Windows Printer Driver(8, 7, XP, 2000, 2003, VISTA, 32&64bit, XP Embedded), WEPOS, OPOS, Linux, JavaPOS	
	DIRECTION	Unidirectional with Friction Feed						
CHARACTER PER LINE	Font A (12 x 24)	36 columns			POWER	TYPE	External SMPS	
	Font B (9 x 17)	48 columns				AC	100 ~ 240Vac 50/60 Hz	
PAPER	TYPE	Thermal Paper				DC	24Vdc / 2.5A	
	WIDTH	59mm ± 0.5mm			AUTO CUTTER	TYPE	Guillotine	
	THICKNESS	0.06mm ~ 0.09mm				LIFE	1,000,000 Cuts	
	ROLL DIAMETER	Max. ø 60mm				PAPER THICKNESS	0.06 ~ 0.09mm	
	ROLL CORE INNER	12.5mm ± 0.5mm				CUTTING METHOD	Partial Cut	
RELIABILITY	TPH LIFE	100Km			TEMPERATURE	OPERATION	0 ~ 45°C	
	MCBF	60,000,000Lines				STORAGE	-20 ~ 60°C	
CHARACTER SET	ALPHANUMERIC CHARACTER	95			HUMIDITY	OPERATION	35 ~ 80%	
	ALPHANUMERIC CHARACTER	128 x 18Page (1 space page)				STORAGE	10 ~ 90%	
	INTERNATIONAL CHARACTER	14			WEIGHT	INCLUDE AUTO CUTTER	0.88kg	
BARCODE		EAN-8, EAN-13, Code 39, ITF, UPC-A, Codabar, Code 93, Code 128, PDF 417(2D)			DIMENSION(W x D X H)		120 x 182 x 106 mm	
					COLOR		Cool grey, Ivory	

● All specification and desings are subject to change without notice.

INTERFACE



ACCESSORY



Melody box



Bnext®

Monterrey | Chihuahua | Ciudad de México | Guadalajara | Mazatlán

Tel. +52 (81) 8881 1080 Ext 1004 Cel. +52 (81) 2747 6654 E-mail. lcardenas@bnext.mx