

sewoo

Mobile Premium Series

SLK-TS400



- Structure for easy maintenance
- Design for enhanced usability
- Compact footprint to help easily fit on the counter.
- Ideal for front exit printing with Wall mount.
- Supports flexible printing exit way Front exit or top exit.
- Ideal for kitchen/bar printer with melody box(Kitchen buzzer)
- Easy handling the jam of the paper with same cover opening/closing direction as paper cutting direction.



WiFi



Bluetooth



Barcode



Portable



Durable



Rugged
Design



Wireless
Connectivity



Easy
Loading



Fast
Speed



Compact
Design



Easy
Maintenance



Improved
Battery Life



APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method
Direct thermal
Print Speed
Up to 8.6ips(220mm/sec)
Print Width
Up to 2.8" (72mm)
Resolution
180 dpi
Power
Power type : External SMPS
AC : 100~240 Vac 50/60Hz
DC : 24 Vdc / 1.75A
Sensor
Paper end, Cover open
Reliability
TPH life : 160km
MCBF : 60 Million lines
Cutter life : 1.5 Million cuts
Drawer port
1 Circuit(24 V, 1A Max.)
Memory
Ram : 8M byte
Flash : 2M byte
NV Image Memory
256 KByte
Receive Buffer
20 KByte
User Define Buffer
4608 Byte



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
5.1"x5.5"x6.0" (130x140x154mm)
Weight
2.7lb(1.25K g)



INTERFACES

Standard
USB(B type)+Serial(RS-232C),
USB(B type)+ Ethernet
Optional
Bluetooth 4.2 classic and Low energy(BLE),
Wi-Fi(802.11 a/b /g/n)
Wi-Fi
WEP, TKIP and AES encryption
WPA and WPA2
802.1x (with WEP, WPA or WPA2)
EAP-TTLS, EAP-TLS, PEAP(MSCHAPv2)
802.11a/b /g/n
Supports Certificates and
Private Key Upload (PEM)
Support for Ad Hoc / Soft AP Mode



OPERATING CHARACTERISTICS

Operating Temperature
32 ~ 113 (0 ~ 45)
Operating Humidity
35 ~ 80%
Storage Temperature
-4 ~ 140 (-20 ~ 60)
Storage Humidity
10 ~ 90%



MEDIA CHARACTERISTICS

Media Type
Thermal paper
Media Width
1.96~3.24"(50~82.5mm)
Media Core Diameter
0.4"(12.5mm)
Media Roll Diameter
3.1"(ø 80mm)
Thickness
0.06~0.09mm



SOFTWARE

Emulations
ESC/POS
Drivers
Windows Driver(10, 2012, 8, 7, 2008,
VISTA, 2003, XP, 32bit & 64bit),
Windows CE & Mobile Driver & SDK
(CE 4.2~, Mobile 5.0~), Linux Driver,
Mac Driver, OPOS Driver, JavaPOS Driver
SDK
iOS, Android(2.1~), Windows, Linux,
BlackBerry, Symbian



BAR CODES

1D
Code 11, Code39, Code 93, Codabar,
ISBT-128, UPC-A, UPC-E, EAN-8,
EAN-13, Code128 with subsets A/B/C,
Interleaved 2-of-5
2D
QR, PDF417, Datamatrix



FONTS / GRAPHICS

Character Type
Font A(12x24), Font B(9x17),
Chinese(Traditional/Simplified, 24x24),
Korean(24x24), Japanese(24x24)
Characters per line (CPL)
Font A(12x24) : 42cpl,
Font B(9x17) : 56cpl,
Chinese/ Korean/Japanese: 21cpl
Character set
95 Alphanumeric,
14 International,
128 x 18 Graphic



ACCESSORIES

Standard
Power Adapter 24 Vdc / 1.75A
Option
Melody Box, Wall Mount



Bnext

Monterrey | Chihuahua | Ciudad de México | Guadalajara | Mazatlán

Tel. +52 (81) 8881 1080 Ext 1004 Cel. +52 (81) 2747 6654 E-mail. lcardenas@bnext.mx